

V Series

Cylindrical Lever Lock



Specifications

ANSI : Meets & Exceeds ANSI - A156.2, Series 4000, Grade 2 Standards

UL Listings : UL Listed for "A" Label 3 Hour Fire Doors

ADA Compliance : Meets ADA and ANSI A117.1 accessibility codes

Cycle Testing : Tested to over 2 Million Cycles

Lock Chassis : Steel, Zinc dichromated for Corrosion Resistance

Clutching : Clutching levers standard for Vandal resistance on locking functions

Trim : 5" Solid zinc diecast levers, 3" wrought brass roses (will not cover thru bolt holes)

Lever Return: Anti-sag mechanism with independent lever return springs to prevent lever sag

Handing : Non-Handed - Completely reversible (S-A & S-B lever styles are handed)

Backset & Latchface : 2 3/8" backset std. with 1" x 2 1/4" latchface, 2 3/4" backset is available with 1 1/8" x 2 1/4" latchface both with self adjusting front for square or beveled edge doors

Latchbolt : Stainless Steel with 1/2" projection, Deadlocking on keyed functions

Cylinder Options : 6 Pin Solid Brass, C Keyway, 2 Silver Nickel Keys standard

Optional Keyways : 11 popular competitor keyways available with replacement cylinders

Strikes : 2 3/4" T strike & Full lip strike w/ 1/4" R.C. standard, 4 7/8" ASA available

Door Preparation : ANSI A115.2 - 2 1/8" crossbore (no thru bolt holes)

Door Thickness : Factory Set for 1 3/4", can be adjusted to fit 1 3/8" to 2" thick doors

Standard Lever Design : Flat (standard, shown above)(stocked in US26D & US10B)

Other Lever Choices : Curved, Half Curved, S-A & S-B levers available in Lever Kits for stock finishes

Standard Finishes : US26D & US10B (in stock)

Special Order Finishes US3 PVD*, US4, US15, US26 PVD* (PVD = Lifetime Finish)

Fasteners : Combination screws for wood or metal doors & frames

Warranty: Limited Lifetime Warranty



211 Endeavor Drive - PO Box 680
Rogersville, MO 65742
PH 877-258-1262 FX 877-888-0150
www.designhardware.net